

FEATURES

Component	Description
Database API	Increase the security of your facility by accurately registering visitors and screening them against government databases before granting access to your facility with visitor management integration, or integrate with other personnel systems for centralized management of physical access
LDAP database integration	Synchronize physical and logical access and manage from a single point of entry
Role-based users	Control what users view and can access or command
Threat level management	Change building access control based on up to 255 different threat levels
Advanced zone management	Count people in a zone, set min and max occupancy limits, require a Supervisor and prevent passback
Intrusion zone management	Monitor, arm and disarm secured areas
Elevator floor control	Individual floor access control
Intuitive user interface	Featuring context-sensitive help
Web client user interface	System access wherever, whenever you need it without additional client licenses
Configurable wiegand formats	Support for most proximity card formats. Avoid replacing existing credentials when retrofitting systems
Custom reports	Information presented in various formats
Custom graphic / map creation	Create custom graphics to provide operators with quick access to critical information
Video system integration	View and control cameras from the same console as other building functions. Select associated video from the alarm console, or pop-up video when alarms occur
Integrated identity management	Print badges, verify identity by comparing photo with video feed
Database import	Import data from other access control systems or HR databases to quickly populate the database
Alarm escalation	Escalate alarms to remote consoles or email recipients

JENEsys SECURITY SUPERVISOR PLATFORM REQUIREMENTS

The JENEsys Security Supervisor may run acceptably on lower-rated platforms, or may require more powerful platforms, depending on the application, number of data points integrated, data poll rate, number of concurrent users, performance expectations, etc. Minimum platform requirements for a JENEsys Security server:

- **Processor:** Intel® Xeon® CPU E5-2640 x64 (or better), compatible with dual and quad-core processors
- **Operating system:** Windows® 7, Windows 8.1 Enterprise, Windows Server 2008, Windows Server 2012 Standard and 2012 R2 Standard, Windows 10
- **Memory:** 4 GB or more recommended
- **Hard drive:** 500 GB or more recommended
- **Display:** Video card and monitor capable of displaying 1024 x 768 pixel resolution or greater
- **Network support:** Ethernet adapter (10/100 Mb with RJ-45 connector)
- **Connectivity:** Full-time high-speed ISP connection recommended for remote site access (i.e. T1, ADSL, cable modem)

ORDERING INFORMATION

JENEsys Security Supervisor	
Niagara AX Supervisor with JENEsys Security Appliance. Licensed for 32 readers, MySQL and MSSQL database drivers. May be upgraded to include BAS driver functionality with optional upgrade part.	
T-SEC-ENT-6	Small Facility Security Supervisor for up to 6 JENE connections
T-SEC-ENT-100	Medium Facility Security Supervisor for up to 100 JENE connections
T-SEC-ENT-250	Large Facility Security Supervisor for up to 250 JENE connections
JENEsys Security Supervisor integrated	
Niagara AX Supervisor with JENEsys Security Appliance. Licensed for 32 readers, MySQL and MSSQL database drivers. Optional BAS drivers available.	
T-S-AX-10-INT	Small Facility Integrated Security Supervisor for up to 10 JENE connections
T-S-AX-100-INT	Medium Facility Integrated Security Supervisor for up to 100 JENE connections
T-S-AX-250-INT	Large Facility Integrated Security Supervisor for up to 250 JENE connections
JENEsys Security Supervisor additional reader packs SEC-R-16	
16 Reader Pack	
SEC-R-64	64 Reader Pack
SEC-R-256	256 Reader Pack
SEC-R-1024	1,024 Reader Pack
JENEsys Security Supervisor upgrades	
SEC-BAS-U	Upgrade JENEsys Security Supervisor to allow BAS driver functionality
SEC-ENT-U	Upgrade Niagara BAS Supervisor to JENEsys Security Supervisor with MySQL, MS SQL and 32 readers
SEC-U-100	Upgrade JENEsys Security Supervisor from small to medium
SEC-U-250	Upgrade JENEsys Security Supervisor from medium to large
SUP-UP-1	Add one JENE connection to the JENEsys Security Supervisor
JENEsys Security Supervisor video options	
DR-S-AXS-AX	Axis IP Camera Base Supervisor Driver for 16 cameras
DR-S-AXS-4	Additional 4 Camera Block for Axis IP Camera Supervisor Driver
DR-S-DED-AX	Dedicated Micros Base Supervisor Driver for 16 cameras
DR-S-DED-4	Additional 4 Camera Block for Dedicated Micros Supervisor Driver
DR-S-MLS-AX	Milestone Base Supervisor Driver for 16 cameras
DR-S-MLS-4	Additional 4 Camera Block for Milestone System Supervisor Driver
DR-S-RPD-AX	Honeywell Rapid Eye™ Base Supervisor Driver for 16 cameras
DR-S-RPD-4	Additional 4 Camera Block for Honeywell Rapid Eye Supervisor Driver
JENEsys Security Supervisor photo ID	
DR-SEC-S-ASURE	Photo ID Driver – enables photo import and integrated photo ID management. Integrates with SEC-ASURE-ID (HID® Asure ID SDK) software which is required for designing badge templates, printing badges and capturing photos
SEC-ASURE-ID	HID Asure ID SDK Software – used for photo capture, creating badge templates and printing badges
JENEsys Security Supervisor database integration	
DR-S-ISOM	Provides a secure restful interface to integrate with the JENEsys Security Supervisor card holder database. May be used to integrate with Easy Lobby® and other 3rd party systems.
SEC-EL-ACI-Niagara	Easy Lobby Access Control Integration plug-in for Niagara. Requires separately purchased Easy Lobby SVM version 10.
DR-S-LDAP	Provides interface to integrate the JENEsys Security Supervisor card holder database to Active Directory/LDAP. Custom configuration of LDAP/Active Directory Database may be required

ORDERING INFORMATION (CONTINUED)

JENEsys Security Supervisor revision upgrade	
SEC-REV-6	Security Small Building Revision Upgrade to current Niagara AX version
SEC-REV-100	Security Supervisor Revision Upgrade to current Niagara AX version
SEC-REV-250	Security Large System Revision Upgrade to current Niagara AX version
JENEsys Security Supervisor maintenance	
Effective for one Maintenance Term (a period of at least 12 months, as defined in the Software Maintenance Terms and Conditions). Upgrades licenses to Niagara 4 releases issued during the Maintenance Term for which the maintenance is purchased. Subject to the Software Maintenance Terms and Conditions.	
SEC-ENT-6-MA	Security Small Building Maintenance for 1 term
SEC-ENT-100-MA	Security Supervisor Maintenance for 1 term
SEC-ENT-250-MA	Security Large System Maintenance for 1 term
JENEsys Security JENE 8000 application	
SEC-J8-AX	Niagara AX Security license for JENE 8000 controller. Includes licensing for 32 readers (not included in capacity). And JENE 8000 Niagara AX license option. (JENE-8000-AX). Does not include JENE 8000 controller.
JENEsys Security JENE accessories	
T-SEC-R2R	Security module for 2 Readers/Access doors and 2 digital inputs
T-SEC-RIO	Security module with 8 supervised inputs, 8 relay outputs and 2 digital inputs
SEC-INT-Keypad	Intrusion keypad with LCD display for arming/disarming security zones
T-SEC-ENC-LNP	Large Enclosure with keyed lock, door status switch, 2 din rails for mounting JENE 8000 controller and up to 4 Remote Reader Modules or 2 Remote IO Modules. Several other combinations of devices may be mounted in this panel. Dimensions: 17"W x 22"H x 4"D.
T-NPB-PWR	DIN rail mountable power supply. 24 VAC/VDC input, 15 VDC 30 VA output. May be used to power modules from the same battery-backed 24 VDC power supply that is used for the JENE.
T-NPB-PWR-UN	DIN rail mountable power supply. Universal input accepts 90-263 VAC 50/60Hz input, 15 VDC 30 Watt output. May be used to power modules where battery backup is not required.
JENEsys Security JENE 602/616 video drivers	
DR-AXS-AX-4	Axis IP camera driver for 4 cameras
DR-DED-AX-4	Dedicated Micros video driver for 4 cameras
DR-MLS-AX-4	Milestone video driver for 4 cameras
DR-RPD-AX-4	Honeywell RapidEye™ video driver for 4 cameras
Access control integration drivers	
DR-ISOM	Driver for Easy Lobby Visitor Management System on JENEsys Security JENE. Does not include Easy Lobby Visitor Management Software.
DR-LDAP	Provides interface to integrate the JENEsys Security JENE card holder database to Active Directory/LDAP. Custom configuration of LDAP/Active Directory Database may be required.

SPECIFICATIONS

	JENEsys Security Supervisor	T-SEC-J-602/616, JENE-8000
Personnel	1,000,000	20,000
Card readers	10,000	32
Access rights	25,000	250
Schedules	1,500	100
Access zones	25,000	50
Simultaneous users	25	10
Area controllers	250	N/A

AGENCY CERTIFICATIONS

T-SEC-J-602, T-SEC-J-616, T-SEC-R2R, T-SEC-RIO, T-NPB-PWR-UN JENEsys Security Field hardware parts are listed as compliant for the following:

- UL 294 – Access Control System Units
- CSA C22.2 No. 205 – Signal Equipment

JENE 8000:

- UL 916
- CE EN 61326-1
- RCM
- FCC Part 15 Subpart B, Class B
- FCC Part 15 Subpart C
- C-UL listed to Canadian Standards Association (CSA) C22.2 No. 205-M1983 “Signal Equipment”
- 1999/5/EC R&TTE Directive
- CCC
- SRRC
- RSS
- RoHS

Lynxspring, Inc.
1210 NE Windsor Dr.
Lee’s Summit, MO 64086
(816) 347-3500
sales@lynxspring.com

COMPATIBILITY

Niagara AX 3.8u2 or later

- JENEsys Security JENE 602/616 and the JENE 8000 support the JENEsys Security application
- Security JENEs must be at the same version as the enterprise server
- Standard (non-JENEsys Security) JENEs must be at the same or earlier version as the enterprise server; 3.6u4, 3.7u1 and 3.8r and higher are supported

Microsoft® Sequal Server® and Sequal Server Express® 2003 – 2012

MySQL™: Verified with versions up to 5.7.9

Browsers: Internet Explorer® 10 and 11

Current versions of Google Chrome® and Mozilla Firefox® do not support views that require WbApplet

Java® Web Start version 8 Update 73 or later supports WbApplet views without browser support

